


BOWSPRIT FOR GENNAKERS & ASYMETRICAL SPINNAKERS



Fitted-in sheave

from 25 up to 57'

Simple and efficient functioning



Bridle attachment



Automatic locking device

- The central fixing collar is removable from the fixing block. The foredeck is therefore totally free (no more fixed collar in the way).

- Rotating collar captive from the section: removable bowsprit for storage alongside one boat edge

- Easy fixation thanks to an automatic locking device on deck fixing blocks;
- Simple installation (only a short backwards movement is needed to fit the bowsprit on the deck);
- Quick removal & storage on a third fixing block;
- The locking system incorporates an anti-theft device.

- Integrated line stopper for holding the tackline.



integrated line stopper

Complete kit including :

- Aluminium bowsprit with special end fittings : bridle attachment at the front and fixing block device at the back (delivered pre-installed);
- Adjustable Central fixing collar +Deck fitting blocks and two counter plates.

Technical datas and references

ø section (mm)	Total length (mm-feet)	Mini. length inside (mm-feet)	max. length outside (mm-feet)	Use example boat length (feet)	Max sail area (m ²)		Fitting FX+ & FX+SPI models
					Asym. Spi.	Gennaker & code zero	
ø 70	1600	800	800	25-36'	60	37*	1500/2500
ø 80	1800	900	900	36-40'	82	52*	2500/4500
ø 90	1900	950	950	40-47'	102	65*	4500/7000**
ø 100	2000	1000	1000	48-57'	130 / 150*	105*	4500/7000**

*with bridles ** FX+7000 with snap shackle option

Articulating toggle (option) for Gennaker / Code zero furler attachment



Bridle kit (option)



- **Options :** «working» and «parking» deck fittings, deck fitting covers, stemhead fittings, bridle kits, furler fitting ring (Gennaker attachment,...),...