You will find within the two ranges of headsail furling and reefing systems (LS-RX), the Facnor product adapted to your needs either cruising, ocean navigation or racing.

	Ranges	
Features	**LS**	**RX**
Removable drum		■
Classic drum	■	
Aluminium feeder	■	■
Rotating tack fitting		■
Fixed tack fitting	■	
Round sections RX	■	
Elliptical sections SX		■

"CRUISING" RANGE LS

LS cruising programm : widely tested range with rounded sections, classic drum, aluminium feeder and fixed tack fitting.

Model	LS 60	LS 70	LS 100	LS 130	LS 165	LS180	LS 200	LS290	LS330
Boat length (meters & feet)	5,5 ↓ 7 m	6,5 ↓ 8 m	7,5 ↓ 9 m	8 ↓ 11 m	9 ↓ 12 m	10 ↓ 13 m	11,5 ↓ 14 m	13 ↓ 18 m	15 ↓ 28 m
	20' ↓ 23'	21' ↓ 28	24' ↓ 29'	26' ↓ 36'	29' ↓ 40'	40' ↓ 43'	38' ↓ 45'	43' ↓ 60'	50' ↓ 90'
max. forestay ø (mm & inch)	5	5	6	6 -7*	8-10*	8-10*	10-12*	12-14*	14-22*
	5/32"	5/32"	1/4"	1/4" 9/32" *	5/16" 3/8" *	5/16" 3/8" *	3/8" 1/2" *	1/2" 9/16" *	9/16" 3/4" *
Section Weight (g/m)	SX 25 577	SX 25 577	SX 33 658	SX 33 658	SX 39 914	SX 39 914	SX 47 1095	SX 47 1095	SX 53 1413
Halyard swivel	C25	C25	C 33	C 33	C 39	C 39	C 47	C 47	C 600
Options	link plates / turnbuckle								

*necessary to have removable eye or turnbuckle

Removable drum : system used as a simple head foil

Just a few minutes are needed to change the furling system into a twin groove head foil ready for racing.

«RACING» RX RANGE- REMOVABLE DRUM

RX racing/cruising program : The aerodynamic sections, the rotating tack fitting and the removable drum plates make the RXs well adapted for racing.

Model	RX 70	RX 100	RX 130	RX 165	RX 220	RX260	RX300
Boat length (meters & feet)	6,5 ↓ 8 m	7,5 ↓ 8,5 m	8 ↓ 9,5 m	9 ↓ 11,5 m	10 ↓ 12,5 m	11,5 ↓ 15 m	13 ↓ 18 m
	21' ↓ 24'	24' ↓ 29'	28' ↓ 30'	29' ↓ 37'	32' ↓ 42'	37' ↓ 49'	42' ↓ 60'
max. forestay ø (mm & inch)	5	6	6 or 7	8	8 or 10	10	12,7
	5/32"	1/4"	1/4" or 9/32"	5/16'	5/16" or 3/8"	3/8'	1/2'
	Necessary to have removable eye or turnbuckle						
Section: Weight (g /m)	R 14 451	R 14 451	R 14 451	R 24 555	R 26 641	R 26 641	R 34 991
Halyard swivel	C 14	C 14	C 14	C 24	C 26	C 26	C 34
Options	link plates / turnbuckle						

1. Unscrew and remove the furling line guide



2.Remove the half plates

3.Fit the two half protection rings

4. Once the half plates are removed, a racing Genoa can be hoisted using the twin groove head foil